

.GB

Page 1 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.04.2020 / 0001

Replacing version dated / version: 09.04.2020 / 0001

Valid from: 09.04.2020 PDF print date: 09.04.2020 Perfect Line Dust Control

# Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

#### **Perfect Line Dust Control**

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Coating

#### **Uses advised against:**

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

Œ

Perfect Line P.O. Box 90117 5000 LA Tilburg (Netherlands) +31(0)857441118 info@perfectline.nl www.perfectline.eu

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

Emergency information services / official advisory body:

---

#### Telephone number of the company in case of emergencies:

During business hours (Monday - Friday 08.00 - 17.00), telephone: +31 (0)857441118

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)
Hazard class Hazard category Hazard statement

Eye Irrit. 2 H319-Causes serious eye irritation.

#### 2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)





Page 2 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.04.2020 / 0001

Replacing version dated / version: 09.04.2020 / 0001

Valid from: 09.04.2020 PDF print date: 09.04.2020 Perfect Line Dust Control

H319-Causes serious eye irritation.

P280-Wear eye protection / face protection.

P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313-If eye irritation persists: Get medical advice / attention.

EUH208-Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

#### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

## **SECTION 3: Composition/information on ingredients**

#### 3.1 Substance

## n.a. **3.2 Mixture**

Propan-2-ol	
Registration number (REACH)	01-2119457558-25-XXXX
Index	603-117-00-0
EINECS, ELINCS, NLP	200-661-7
CAS	67-63-0
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 2, H225
	Eye Irrit. 2, H319
	STOT SE 3, H336

Reaction products of 1H-Imidazole-1-ethanol, 4,5-dihydro-, 2-(C7-C17 odd-numbered, C17-unsatd. alkyl) derivs. and sodium hydroxide and chloroacetic acid	
Registration number (REACH)	01-2119487973-19-XXXX
Index	
EINECS, ELINCS, NLP	931-291-0 (REACH-IT List-No.)
CAS	
content %	1-<3
Classification according to Regulation (EC) 1272/2008 (CLP)	Eye Dam. 1, H318

Pyridine-2-thiol 1-oxide, sodium salt	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	223-296-5
CAS	3811-73-2
content %	0,001-<0,1
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H302
	Acute Tox. 4, H332
	Eye Dam. 1, H318
	Aquatic Acute 1, H400 (M=100)
	Aquatic Chronic 2, H411

61540-60-XXXX
00-6
9
5



(B)

Page 3 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.04.2020 / 0001

Replacing version dated / version: 09.04.2020 / 0001

Valid from: 09.04.2020 PDF print date: 09.04.2020 Perfect Line Dust Control

content %	0,001-<0,01
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H302
	Skin Irrit. 2, H315
	Skin Sens. 1, H317
	Eye Dam. 1, H318
	Acute Tox. 2, H330
	Aquatic Acute 1, H400 (M=10)
	Aquatic Chronic 2, H411

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

#### **SECTION 4: First aid measures**

## 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### **Eve contact**

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

## 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

The following may occur:

eyes, reddened

Watering eyes

reddening of the skin

Allergic reaction

#### 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

#### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

### Suitable extinguishing media

Water jet spray/foam/CO2/dry extinguisher

#### Unsuitable extinguishing media

High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of nitrogen

Toxic gases

#### 5.3 Advice for firefighters



Œ

Page 4 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.04.2020 / 0001

Replacing version dated / version: 09.04.2020 / 0001

Valid from: 09.04.2020 PDF print date: 09.04.2020 Perfect Line Dust Control

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire Full protection, if necessary. Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.

Remove possible causes of ignition - do not smoke.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

#### **6.2 Environmental precautions**

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

If accidental entry into drainage system occurs, inform responsible authorities.

#### 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13. Do not wash away with water or watery cleaning agents.

#### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

#### **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

#### 7.1 Precautions for safe handling

## 7.1.1 General recommendations

Ensure good ventilation.

Avoid inhalation of the vapours.

Avoid contact with eyes or skin.

Keep away from sources of ignition - Do not smoke.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Store product closed and only in original packing.

Not to be stored in gangways or stair wells.

Protect from direct sunlight and warming.

Store in a well-ventilated place.

#### 7.3 Specific end use(s)

No information available at present.

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters



Page 5 of 17 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.04.2020 / 0001

Replacing version dated / version: 09.04.2020 / 0001 Valid from: 09.04.2020

® Chemical Name	Propan-2-ol			Content %:1- <10
WEL-TWA: 400 ppm (999 mg/n	n3)	WEL-STEL: 500 ppm (1250 mg/m3)		
Monitoring procedures:	-	Compur - KITA-122 SA(C) (549 277)		
	-	Compur - KITA-150 U (550 382)		
	-	Draeger - Alcohol 25/a i-Propanol (81 01 631)		
		DFG (D) (Loesungsmittelgemische), DFG (E) (Solvent r	nixtures	6) - 1998, 2002 -
	-	EU project BC/CEN/ENTR/000/2002-16 card 66-3 (2004)	4)	,
	-	Draeger - Alcohol 100/a (CH 29 701)	•	
BMGV:		Other information:		
© Chamical Name	Chromina			Contant 0/:

Chemical Name	Glycerine			Content %:
WEL-TWA: 10 mg/m3 (mist)		WEL-STEL:		
Monitoring procedures:	-	- <b>-</b>		
BMGV:			Other information:	

Area of application	Exposure route / Environmental	Effect on health	Descripto	Value	Unit	Note
	compartment		•			
	Environment - freshwater		PNEC	140,9	mg/l	
	Environment - marine		PNEC	140,9	mg/l	
	Environment - sediment, freshwater		PNEC	552	mg/kg	
	Environment - sediment, marine		PNEC	552	mg/kg	
	Environment - soil		PNEC	28	mg/kg	
	Environment - sewage treatment plant		PNEC	2251	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	140,9	mg/l	
	Environment - oral (animal feed)		PNEC	160	mg/kg feed	
Consumer	Human - dermal	Long term	DNEL	319	mg/kg	(1 d)
Consumer	Human - inhalation	Long term	DNEL	89	mg/m3	, , ,
Consumer	Human - oral	Long term	DNEL	26	mg/kg	(1 d)
Workers / employees	Human - dermal	Long term	DNEL	888	mg/kg	(1 d)
Workers / employees	Human - inhalation	Long term	DNEL	500	mg/m3	

rea of application	Exposure route /	Effect on health	Descripto	Value	Unit	Note
	Environmental		r			
	compartment					
	Environment - freshwater		PNEC	0,0053	mg/l	
	Environment - marine		PNEC	0,00053	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	0,053	mg/l	
	Environment - sewage treatment plant		PNEC	6,6	mg/l	
	Environment - sediment, freshwater		PNEC	0,0208	mg/kg	
	Environment - sediment, marine		PNEC	0,00208	mg/kg	
	Environment - soil		PNEC	0,00104	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	4,06	mg/m3	



Œ

Page 6 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.04.2020 / 0001

Replacing version dated / version: 09.04.2020 / 0001

Valid from: 09.04.2020 PDF print date: 09.04.2020 Perfect Line Dust Control

Consumer	Human - dermal	Long term, systemic effects	DNEL	3,85	mg/kg bw/d	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,39	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	4,5	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	6,42	mg/kg bw/d	

Glycerine						
Area of application	Exposure route / Environmental compartment	Effect on health	Descripto r	Value	Unit	Note
	Environment - freshwater		PNEC	0,885	mg/l	
	Environment - marine		PNEC	0,088	mg/l	
	Environment - sewage treatment plant		PNEC	1000	mg/l	
	Environment - sediment, freshwater		PNEC	3,3	mg/kg dw	
	Environment - sediment, marine		PNEC	0,33	mg/kg dw	
	Environment - soil		PNEC	0,141	mg/kg dw	
Consumer	Human - inhalation	Long term, local effects	DNEL	33	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	229	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	56	mg/m3	

- WEL-TWA = Workplace Exposure Limit Long-term exposure limit (8-hour TWA (= time weighted average) reference period)
  FH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany)
- EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

  (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit Short-term exposure limit (15-minute reference period).
- (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
- \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision. (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

#### 8.2 Exposure controls

#### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

#### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.



Page 7 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.04.2020 / 0001

Replacing version dated / version: 09.04.2020 / 0001

Valid from: 09.04.2020 PDF print date: 09.04.2020 Perfect Line Dust Control

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eve/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN 374).

Recommended

Safety gloves made of butyl (EN 374)

Protective nitrile gloves (EN 374).

Minimum layer thickness in mm:

Permeation time (penetration time) in minutes:

>= 480

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Unsuitable material:

Cotton gloves

Leather gloves

Skin protection - Other:

Usual protective working garments

Respiratory protection:

If OES or MEL is exceeded.

Gas mask filter A (EN 14387), code colour brown

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

#### 8.2.3 Environmental exposure controls

No information available at present.

#### **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Physical state: Liquid Colour: Colourless Odour: Characteristic Odour threshold: Not determined pH-value: 10,2 (20°C) Melting point/freezing point: Not determined Initial boiling point and boiling range: Not determined >93 °C Flash point:

Evaporation rate: Not determined

Flammability (solid, gas): n.a. 2 Vol-% Lower explosive limit: Upper explosive limit: 12 Vol-% Vapour pressure: 43 hPa (20°C) Vapour density (air = 1): Not determined



(GB)

Page 8 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.04.2020 / 0001

Replacing version dated / version: 09.04.2020 / 0001

Valid from: 09.04.2020 PDF print date: 09.04.2020 Perfect Line Dust Control

Density: ~1 g/cm3 (20°C)

Bulk density: n.a.

Solubility(ies): Not determined

Water solubility: Mixable

Partition coefficient (n-octanol/water):

Not determined

Auto-ignition temperature: 425 °C (Ignition temperature )

Decomposition temperature:

Viscosity:

Not determined

Not determined

Explosive properties: Product is not explosive. When using: development of explosive

No

vapour/air mixture possible.

Oxidising properties:

9.2 Other information

Miscibility:

Fat solubility / solvent:

Conductivity:

Surface tension:

Solvents content:

Not determined
Not determined
Not determined
Not determined
Not determined

## **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

Not to be expected

#### 10.2 Chemical stability

Stable with proper storage and handling.

## 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

#### 10.4 Conditions to avoid

See also section 7.

None known

#### 10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

Avoid contact with strong alkalis.

Avoid contact with strong acids.

## 10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

### **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Perfect Line Dust Control			·			
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal						n.d.a.
route:						
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye						n.d.a.
damage/irritation:						
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						



Page 9 of 17 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.04.2020 / 0001

Replacing version dated / version: 09.04.2020 / 0001 Valid from: 09.04.2020

Specific target organ toxicity - repeated exposure (STOT-RE):			n.d.a.
Aspiration hazard:			n.d.a.
Symptoms:			n.d.a.

Propan-2-ol	I	T				Las
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	4570-5840	mg/kg	Rat	OECD 401 (Acute	
					Oral Toxicity)	
Acute toxicity, by dermal	LD50	13900	mg/kg	Rabbit	OECD 402 (Acute	
route:					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	30	mg/l/4h	Rat		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye				Rabbit	OECD 405 (Acute	Eye Irrit. 2
damage/irritation:					Eye	
<b>G</b>					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin
sensitisation:					Sensitisation)	contact)
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
John John Malagomony				typhimurium	Reverse Mutation	l regains
				ургштатат	Test)	
Germ cell mutagenicity:				Salmonella	(Ames-Test)	Negative
Com con matagomeny.				typhimurium	(7 11.100 1 001)	rioganio
Germ cell mutagenicity:				Mouse	OECD 474	Negative
Cerm cen managementy.				Wiouse	(Mammalian	ricgative
					Erythrocyte	
					Micronucleus Test)	
Germ cell mutagenicity:					OECD 476 (In Vitro	Negative
Germ cen mutagemony.					Mammalian Cell Gene	ivegative
					Mutation Test)	
Carcinogenicity:					Mutation rest)	Negative
Specific target organ toxicity -						STOT SE 3,
single exposure (STOT-SE):						H336
Specific target organ toxicity -						Target
repeated exposure (STOT-						organ(s): liver
RE):						
Aspiration hazard:						No
Symptoms:						breathing
						difficulties,
						unconsciousnes
						s, vomiting,
						headaches,
						fatigue,
						dizziness,
						nausea
Specific target organ toxicity -	NOAEL	900	mg/kg	Rat	OECD 408 (Repeated	
repeated exposure (STOT-					Dose 90-Day Oral	
RE), oral:					Toxicity Study in	
,,					Rodents)	
Specific target organ toxicity -	NOAEL	5000	ppm	Rat	, , , , , , , , , , , , , , , , , , , ,	Vapours
repeated exposure (STOT-			1			
RE), inhalat.:						

Reaction products of 1H-Imidazole-1-ethanol, 4,5-dihydro-, 2-(C7-C17 odd-numbered, C17-unsatd. alkyl) derivs. and sodium hydroxide and chloroacetic acid								
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes		
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute			
					Oral Toxicity)			
rodio toxiony, by oral rodio.	2200	70000	ing/kg	- Tut	`			



Page 10 of 17 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.04.2020 / 0001

Replacing version dated / version: 09.04.2020 / 0001 Valid from: 09.04.2020

Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye				Rabbit	OECD 405 (Acute	Risk of serious
damage/irritation:					Eye	damage to
-					Irritation/Corrosion)	eyes.
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin
sensitisation:					Sensitisation)	contact)
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative
					Reverse Mutation	
					Test)	
Germ cell mutagenicity:					OECD 473 (In Vitro	Negative
					Mammalian	
					Chromosome	
					Aberration Test)	
Germ cell mutagenicity:					OECD 476 (In Vitro	Negative
					Mammalian Cell Gene	
					Mutation Test)	
Aspiration hazard:						No
Specific target organ toxicity -	NOAEL	92,5	mg/kg	Rat	OECD 407 (Repeated	
repeated exposure (STOT-			bw/d		Dose 28-Day Oral	
RE), oral:					Toxicity Study in	
					Rodents)	

1,2-benzisothiazol-3(2H)-one										
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes				
Acute toxicity, by oral route:	LD50	1020	mg/kg	Rat						
Acute toxicity, by dermal	LC50	>2000	mg/kg	Rat						
route:										
Acute toxicity, by inhalation:	LC50	0,4	mg/l/4h	Rat		Aerosol				
Skin corrosion/irritation:						Irritant				
Serious eye						Eye Dam. 1				
damage/irritation:										
Respiratory or skin				Guinea pig	OECD 406 (Skin	Sensitising				
sensitisation:					Sensitisation)	(skin contact)				

Glycerine						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat		
Acute toxicity, by dermal	LD50	>10000	mg/kg	Rabbit		
route:						
Skin corrosion/irritation:				Rabbit	IUCLID Chem. Data Sheet (ESIS)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	mmanory correcting	Not sensitizising
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity:	NOAEL	2000	mg/kg/d		·	Negative
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	3,91	mg/l	Rat		14d
Aspiration hazard:						Negative



(B)

Page 11 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.04.2020 / 0001

Replacing version dated / version: 09.04.2020 / 0001

Valid from: 09.04.2020 PDF print date: 09.04.2020 Perfect Line Dust Control

Symptoms:			abdominal
			pain,
			drowsiness,
			diarrhoea,
			vomiting,
			headaches,
			mucous
			membrane
			irritation

## **SECTION 12: Ecological information**

Possibly more information on environmental effects, see Section 2.1 (classification).

Perfect Line Dust Con	trol						
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to							n.d.a.
daphnia:							
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							n.d.a.
degradability:							
12.3. Bioaccumulative							n.d.a.
potential:							
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Other adverse							n.d.a.
effects:							

Propan-2-ol Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to bacteria:	EC10	16h	1050	mg/l	Pseudomonas		
•					putida		
12.1. Toxicity to daphnia:	EC50	16d	141	mg/l	Daphnia magna		
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Leuciscus idus		
12.1. Toxicity to fish:	LC50	96h	1400	mg/l	Lepomis macrochirus		
12.1. Toxicity to daphnia:	EC50	48h	2285	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Desmodesmus subspicatus		
12.2. Persistence and degradability:		21d	95	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	Readily biodegradable
12.2. Persistence and degradability:			99,9	%		OECD 303 A (Simulation Test - Aerobic Sewage Treatment - Activated Sludge Units)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		0,05			OECD 107 (Partition Coefficient (n- octanol/water) - Shake Flask Method)	Slight



Page 12 of 17 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.04.2020 / 0001

Replacing version dated / version: 09.04.2020 / 0001 Valid from: 09.04.2020

12.5. Results of PBT					No PBT
and vPvB assessment					substance, No
					vPvB substance
12.4. Mobility in soil:	Koc	1,1			Expert
-					judgement
Toxicity to bacteria:	EC50	>1000	mg/l	activated sludge	
Other information:	ThOD	2,4	g/g		
Other information:	BOD5	53	%		
Other information:	COD	96	%		References
Other information:	COD	2,4	g/g		
Other information:	BOD	1171	mg/g		

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance
12.1. Toxicity to fish:	LC50	96h	4,2	mg/l	Oncorhynchus	OECD 203	
					mykiss	(Fish, Acute	
						Toxicity Test)	
12.1. Toxicity to fish:	LC50	96h	8,5	mg/l	Brachydanio rerio	OECD 203	
						(Fish, Acute	
						Toxicity Test)	
12.1. Toxicity to	EC50	48h	2,5	mg/l	Daphnia magna	OECD 202	
daphnia:						(Daphnia sp.	
•						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to algae:	EC50	72h	30	mg/l	Desmodesmus	OECD 201	
					subspicatus	(Alga, Growth	
						Inhibition Test)	
12.1. Toxicity to algae:	EC50	72h	16,9	mg/l	Pseudokirchnerie	84/449/EEC C.3	
					lla subcapitata		
12.2. Persistence and		28d	100	%	·	OECD 311	
degradability:						(Anaerobic	
						Biodeg. of	
						Organic Comp.	
						in Digested	
						Sludge - by	
						Measurement of	
						Gas Production)	
12.2. Persistence and		28d	79	%	activated sludge	OECD 301 F	Readily
degradability:						(Ready	biodegradable
,						Biodegradability -	
						Manometric	
						Respirometry	
						Test)	
Toxicity to bacteria:	NOEC/NOEL		12,7	g/l	Pseudomonas	DIN 38412 T.8	
,					putida		
Other information:	COD		720	g/l		DIN 38409-H41	

1,2-benzisothiazol-3(2H)-one											
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes				
12.1. Toxicity to algae:	EC50	72h	0,0403	mg/l	Pseudokirchnerie Ila subcapitata	OECD 201 (Alga, Growth Inhibition Test)					



Page 13 of 17 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.04.2020 / 0001

Replacing version dated / version: 09.04.2020 / 0001 Valid from: 09.04.2020

		6.	1.5			0505.000
Toxicity to bacteria:	EC50	3h	13	mg/l	activated sludge	OECD 209
						(Activated
						Sludge,
						Respiration
						Inhibition Test
						(Carbon and
						Ammonium
						Oxidation))
12.1. Toxicity to fish:	LC50	96h	2,18	mg/l	Oncorhynchus	OECD 203
_					mykiss	(Fish, Acute
						Toxicity Test)
12.1. Toxicity to	EC50	48h	2,94	mg/l	Daphnia magna	OECD 202
daphnia:			,			(Daphnia sp.
						Acute
						Immobilisation
						Test)
12.2. Persistence and			90	%	activated sludge	OECD 302 B
degradability:				, , ,	aon raisa sidage	(Inherent
aogradasy.						Biodegradability -
						Zahn-
						Wellens/EMPA
						Test)
12.2. Persistence and	DOC		>70	%	activated sludge	OECD 303 A
degradability:	000		//0	70	activated studge	(Simulation Test -
degradability.						Aerobic Sewage
						Treatment -
						Activated Sludge
						Units)
12.3. Bioaccumulative	BCF		6,95			OECD 305
potential:	BCI		0,95			(Bioconcentration
poteritiai.						- Flow-Through
						Fish Test)
12.3. Bioaccumulative			0,7			OECD 117
			0,7			(Partition
potential:						
						Coefficient (n-
						octanol/water) -
<del>-</del> · · · · · · · · · · · · · · · · · · ·	F000	01		,		HPLC method)
Toxicity to bacteria:	EC20	3h	3,3	mg/l	activated sludge	OECD 209
						(Activated
						Sludge,
						Respiration
						Inhibition Test
						(Carbon and
						Ammonium
						Oxidation))

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and degradability:	BOD5		0,87	g/g			
12.2. Persistence and degradability:	COD		1,16	g/g			
12.1. Toxicity to fish:	LC50	96h	> 5000	mg/l	Carassius auratus		
12.1. Toxicity to daphnia:	EC50	48h	>10000	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	EC5	72h	3200	mg/l			Entosiphon sulcatum
12.1. Toxicity to algae:	EC50		2900	mg/l	Chlorella vulgaris		



Œ

Page 14 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.04.2020 / 0001

Replacing version dated / version: 09.04.2020 / 0001

Valid from: 09.04.2020 PDF print date: 09.04.2020 Perfect Line Dust Control

12.2. Persistence and degradability:		14d	63	%		OECD 301 C (Ready Biodegradability - Modified MITI Test (I))	
12.2. Persistence and degradability:	BOD/COD		>60	%			
12.2. Persistence and degradability:	BOD5/COD		> 50	%			
12.2. Persistence and degradability:	DOC		>70	%			Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		-1,76				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC5	16h	> 10000	mg/l	Pseudomonas putida		

#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

#### For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

## **SECTION 14: Transport information**

#### **General statements**

14.1. UN number: n.a.

#### Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Classification code:n.a.LQ:n.a.

14.5. Environmental hazards:

Not applicable

Tunnel restriction code:

## Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.



Page 15 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.04.2020 / 0001

Replacing version dated / version: 09.04.2020 / 0001

Valid from: 09.04.2020 PDF print date: 09.04.2020 Perfect Line Dust Control

14.4. Packing group: n.a. Marine Pollutant: n.a

14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a. 14.4. Packing group: n.a.

14.5. Environmental hazards: Not applicable

#### 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

#### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

#### **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)! Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): 7,5 %

#### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

#### **SECTION 16: Other information**

Revised sections:

n.a.

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

## Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Eye Irrit. 2, H319	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H330 Fatal if inhaled.

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

Eye Irrit. — Eye irritation

Flam. Liq. — Flammable liquid STOT SE — Specific target organ toxicity - single exposure - narcotic effects

Eye Dam. — Serious eye damage Acute Tox. — Acute toxicity - oral



(B)

Page 16 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.04.2020 / 0001

Replacing version dated / version: 09.04.2020 / 0001

Valid from: 09.04.2020 PDF print date: 09.04.2020 Perfect Line Dust Control

Acute Tox. — Acute toxicity - inhalation

Aquatic Acute — Hazardous to the aquatic environment - acute Aquatic Chronic — Hazardous to the aquatic environment - chronic

Skin Irrit. — Skin irritation Skin Sens. — Skin sensitization

#### Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAUA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level DNEL Derived No Effect Level

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community
ECHA European Chemicals Agency
EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

etc. et cetera EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

IARC International Agency for Research on Cancer

IATA International Air Transport Association
IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

**IUCLIDInternational Uniform Chemical Information Database** 

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicablen.av. not availablen.c. not checkedn.d.a. no data available

OECD Organisation for Economic Co-operation and Development

org. organic

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million PVC Polyvinylchloride



GB)

Page 17 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 09.04.2020 / 0001

Replacing version dated / version: 09.04.2020 / 0001

Valid from: 09.04.2020 PDF print date: 09.04.2020 Perfect Line Dust Control

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

## Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.