

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier
- Trade name: **Perfect Line Uni Thinner**
  
- Article number: PL.UNI.5 / PL.UNI.1
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Sector of Use
  - SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
  - SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- Application of the substance / the mixture Thinner, Diluent
- Uses advised against SU21 Consumer uses: Private households / general public / consumers
  
- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
  - Perfect Line
  - Postbus 90117
  - 5000 LA TILBURG
  - Holland
  - T +31 (0)857441118
  - E info@perfectline.nl
  - W www.perfectline.nl
- Further information obtainable from: Product safety department: info@perfectline.nl
- 1.4 Emergency telephone number:
  - National Poisoning Information Centre - Bilthoven - The Netherlands
  - T +31 (0)30 274 88 88
  - Restricted to physicians for information on ingredients.

## SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3	H226	Flammable liquid and vapour.
--------------	------	------------------------------



GHS08 health hazard

STOT RE 2	H373	May cause damage to the central nervous system, the kidneys and the liver through prolonged or repeated exposure. Route of exposure: Inhalation.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
STOT SE 3	H335-H336	May cause respiratory irritation. May cause drowsiness or dizziness.
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008  
The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Trade name: **Perfect Line Uni Thinner**

(Contd. of page 1)

## · Hazard pictograms



GHS02    GHS07    GHS08

## · Signal word Danger

## · Hazard-determining components of labelling:

xylene  
n-butyl acetate

## · Hazard statements

- H226      Flammable liquid and vapour.  
 H315      Causes skin irritation.  
 H319      Causes serious eye irritation.  
 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.  
 H373      May cause damage to the central nervous system, the kidneys and the liver through prolonged or repeated exposure. Route of exposure: Inhalation.  
 H304      May be fatal if swallowed and enters airways.  
 H412      Harmful to aquatic life with long lasting effects.

## · Precautionary statements

- P243      Take action to prevent static discharges.  
 P260      Do not breathe mist/vapours/spray.  
 P280      Wear protective gloves/protective clothing/eye protection/face protection.  
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

## · Additional information:

Restricted to professional users.

## · 2.3 Other hazards

## · Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

## · 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

## · Dangerous components %(m/m):

CAS: 123-86-4	n-butyl acetate	25-50%
EINECS: 204-658-1	☞ Flam. Liq. 3, H226; ☞ STOT SE 3, H336	
Reg.nr.: 01-2119485493-29		
CAS: 108-65-6	2-methoxy-1-methylethyl acetate	25-50%
EINECS: 203-603-9	☞ Flam. Liq. 3, H226	
Reg.nr.: 01-2119475791-29		
CAS: 1330-20-7	xylene	25-50%
EINECS: 215-535-7	☞ Flam. Liq. 3, H226; ☞ STOT RE 2, H373; Asp. Tox. 1, H304; ☞ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	
Reg.nr.: 01-2119488216-32		
CAS: 100-41-4	ethylbenzene	2.5-10%
EINECS: 202-849-4	☞ Flam. Liq. 2, H225; ☞ STOT RE 2, H373; Asp. Tox. 1, H304; ☞ Acute Tox. 4, H332; Aquatic Chronic 3, H412	
Reg.nr.: 01-2119489370-35		

(Contd. on page 3)

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 22.03.2019

Version number 8

Revision: 14.07.2017

Trade name: **Perfect Line Uni Thinner**

(Contd. of page 2)

CAS: 108-88-3          toluene          ≤ 0.5%  
EINECS: 203-625-9          ⚠ Flam. Liq. 2, H225; ⚠ Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304;  
Reg.nr.: 01-2119471310-51          ⚠ Skin Irrit. 2, H315; STOT SE 3, H336  
· Additional information: For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures**

- 4.1 Description of first aid measures
- General information:  
Immediately remove any clothing soiled by the product.  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.  
Remove contactlenses.
- After swallowing:  
Do not induce vomiting; call for medical help immediately.  
Rinse mouth.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed  
No further relevant information available.

**SECTION 5: Firefighting measures**

- 5.1 Extinguishing media
- Suitable extinguishing agents: CO2 or powder. Fight larger fights with alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture  
During heating or in case of fire poisonous gases are produced.  
Carbon monoxide (CO)
- 5.3 Advice for firefighters
- Protective equipment: Wear self-contained respiratory protective device.

**SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions:  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- 6.4 Reference to other sections  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

**SECTION 7: Handling and storage**

- 7.1 Precautions for safe handling  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.

(Contd. on page 4)  
— EU —

Trade name: **Perfect Line Uni Thinner**

(Contd. of page 3)

- Information about fire - and explosion protection:  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Keep respiratory protective device available.
- 7.2 Conditions for safe storage, including any incompatibilities
- Storage:  
Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- Information about storage in one common storage facility: Store away from oxidising agents.
- Further information about storage conditions: Keep container tightly sealed.
- Storage class: 3
- 7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

### 108-65-6 2-methoxy-1-methylethyl acetate

IOELV Short-term value: 550 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 275 mg/m<sup>3</sup>, 50 ppm  
Skin

### 1330-20-7 xylene

IOELV Short-term value: 442 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 221 mg/m<sup>3</sup>, 50 ppm  
Skin

### 100-41-4 ethylbenzene

IOELV Short-term value: 884 mg/m<sup>3</sup>, 200 ppm  
Long-term value: 442 mg/m<sup>3</sup>, 100 ppm  
Skin

- DNELs

### 123-86-4 n-butyl acetate

Inhalative Acute - short-term exposure - systemic effects	600 mg/m <sup>3</sup> (worker)
Acute - short-term exposure - local effects	600 mg/m <sup>3</sup> (worker)
Long-term exposure - systemic effects	300 mg/m <sup>3</sup> (worker)
Long-term exposure - local effects	300 mg/m <sup>3</sup> (worker)

### 108-65-6 2-methoxy-1-methylethyl acetate

Dermal Long-term exposure - systemic effects	153.5 mg/kg bw/day (worker)
Inhalative Long-term exposure - systemic effects	275 mg/m <sup>3</sup> (worker)

### 1330-20-7 xylene

Dermal Long-term exposure - systemic effects	180 mg/kg bw/day (worker)
Inhalative Acute - short-term exposure - systemic effects	289 mg/m <sup>3</sup> (worker)
Acute - short-term exposure - local effects	289 mg/m <sup>3</sup> (worker)
Long-term exposure - systemic effects	77 mg/m <sup>3</sup> (worker)

### 100-41-4 ethylbenzene

Dermal Acute - short-term exposure - local effects	293 mg/kg bw/day (worker)
Long-term exposure - systemic effects	180 mg/kg bw/day (worker)
Inhalative Long-term exposure - systemic effects	77 mg/m <sup>3</sup> (worker)

(Contd. on page 5)

Trade name: **Perfect Line Uni Thinner**

(Contd. of page 4)

**108-88-3 toluene**

Dermal	Long-term exposure - systemic effects	384 mg/kg bw/day (worker)
Inhalative	Acute - short-term exposure - systemic effects	384 mg/m <sup>3</sup> (worker)
	Acute - short-term exposure - local effects	384 mg/m <sup>3</sup> (worker)
	Long-term exposure - systemic effects	192 mg/m <sup>3</sup> (worker)
	Long-term exposure - local effects	192 mg/m <sup>3</sup> (worker)

## · PNECs

**123-86-4 n-butyl acetate**

PNEC	0.981 mg/kg (sediment freshwater)
PNEC	35.6 mg/l (STP)
	0.18 mg/l (aqua, freshwater)
	0.36 mg/l (aqua, intermittent releases)
	0.018 mg/l (aqua, marine water)
	0.0981 mg/l (sediment marine water)

**108-65-6 2-methoxy-1-methylethyl acetate**

PNEC	0.329 mg/kg (sediment marine water)
	3.29 mg/kg (sediment freshwater)
	0.29 mg/kg (soil)
PNEC	100 mg/l (STP)
	6.35 mg/l (aqua, intermittent releases)
	0.0635 mg/l (aqua, marine water)
	0.635 mg/l (aqua freshwater)

**1330-20-7 xylene**

PNEC	12.46 mg/kg (sediment marine water)
PNEC	6.58 mg/l (STP)
	0.327 mg/l (aqua, freshwater)
	0.327 mg/l (aqua, marine water)

**100-41-4 ethylbenzene**

PNEC	13.7 mg/kg (sediment freshwater)
	2.68 mg/kg (soil)
PNEC	9.6 mg/l (STP)
	0.1 mg/l (aqua, freshwater)
	0.1 mg/l (aqua, intermittent releases)
	0.01 mg/l (aqua, marine water)

**108-88-3 toluene**

PNEC	16.39 mg/kg (sediment marine water)
	16.39 mg/kg (sediment freshwater)
	2.89 mg/kg (soil)
PNEC	13.61 mg/l (STP)
	0.68 mg/l (aqua, freshwater)
	0.68 mg/l (aqua, intermittent releases)
	0.68 mg/l (aqua, marine water)

· Additional information: The lists valid during the making were used as basis.

## · 8.2 Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

(Contd. on page 6)

Trade name: **Perfect Line Uni Thinner**

(Contd. of page 5)

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Short term filter device:

Filter A.

- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

Suitable materials for safety gloves (EN 374):

Butyl rubber, BR

- Penetration time of glove material

Thickness of the gloves  $\geq 0.3$  mm (butylacetate)Value for the permeation: Level  $\geq 60$  min (butylacetate)

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye protection:



Tightly sealed goggles

- Body protection: Solvent resistant protective clothing

## SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties

- General Information

- Appearance:

Form: Liquid

Colour: Clear

- Odour: Characteristic

- Odour threshold: Not determined.

- pH-value: Not determined.

- Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 124-128 °C

- Flash point: 29 °C

- Flammability (solid, gas): Not applicable.

- Ignition temperature: 315 °C

- Decomposition temperature: Not determined.

- Auto-ignition temperature: Product is not selfigniting.

- Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

(Contd. on page 7)

Trade name: **Perfect Line Uni Thinner**

(Contd. of page 6)

· Explosion limits:	
Lower:	1.1 Vol %
Upper:	10.8 Vol %
· Vapour pressure at 20 °C:	
	10.7 hPa
· Density at 20 °C:	
	0.9 g/cm <sup>3</sup>
· Relative density	
	Not determined.
· Vapour density	
	Not determined.
· Evaporation rate	
	Not determined.
· Solubility in / Miscibility with water:	
	Slightly soluble.
· Partition coefficient: n-octanol/water:	
	Not determined.
· Viscosity:	
Dynamic at 20 °C:	1 mPas
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	100.0 %
VOC (EC)	100.00 %
Solids content:	
	0.0 %
· 9.2 Other information	
	No further relevant information available.

## SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions Reacts with strong oxidizing agents.
- 10.4 Conditions to avoid High temperatures.
- 10.5 Incompatible materials: Oxidizing agents
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.
- LD/LC50 values relevant for classification:

### 123-86-4 n-butyl acetate

Oral LD50 10,760 mg/kg (rat) (OECD 423)  
 Dermal LD50 >14,112 mg/kg (rabbit) (OECD 402)  
 Inhalative LC50/4h 23.4 mg/l (rat) (OECD 403 in vivo, aerosol)

### 108-65-6 2-methoxy-1-methylethyl acetate

Oral LD50 >5,000 mg/kg (rat)  
 Dermal LD50 >5,000 mg/kg (rat)  
 Inhalative LC0/3h >2,000 ppm (rat)

### 1330-20-7 xylene

Oral LD50 3,523 mg/kg (rat)  
 Dermal LD50 12,126 mg/kg bw (rabbit)  
 Inhalative LC50/4h 6,700 ppm (rat)

(Contd. on page 8)

Trade name: **Perfect Line Uni Thinner**

(Contd. of page 7)

**100-41-4 ethylbenzene**

Oral LD50 3,500 mg/kg (rat)  
Dermal LD50 17,800 mg/kg (rabbit)  
Inhalative LC50/4h 17.8 mg/l (rat)

**108-88-3 toluene**

Oral LD50 5,580 mg/kg (rat)  
Dermal LD50 >5,000 mg/kg (rabbit)  
Inhalative LC50/4h 28.1 mg/l (rat)

- Primary irritant effect:
- Skin corrosion/irritation  
Causes skin irritation.
- Serious eye damage/irritation  
Causes serious eye irritation.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure  
May cause respiratory irritation. May cause drowsiness or dizziness.
- STOT-repeated exposure  
May cause damage to the central nervous system, the kidneys and the liver through prolonged or repeated exposure.  
Route of exposure: Inhalation.
- Aspiration hazard  
May be fatal if swallowed and enters airways.

**SECTION 12: Ecological information**

- 12.1 Toxicity
- Aquatic toxicity:

**123-86-4 n-butyl acetate**

EC50/48h 44 mg/l (daphnia magna)  
EC50/72h 647.7 mg/l (desmodesmus supspicatus)  
IC50 356 mg/l (tetrahymena pyriformis) (40 h)  
NOAEL/72h 200 mg/l (desmodesmus supspicatus)  
LC50/96h 18 mg/l (pimphales promelas) (OECD 203)

**108-65-6 2-methoxy-1-methylethyl acetate**

EC50/48h >400 mg/l (daphnia magna)  
LC50/96h 100-180 mg/l (oncorhynchus mykiss)

**1330-20-7 xylene**

IC50/72h 2.2 mg/l (algae)  
NOEC/72h 0.44 mg/l (algae)  
EC50/48h 1 mg/l (daphnia magna)  
LC50/96h 2.6 mg/l (oncorhynchus mykiss)

**100-41-4 ethylbenzene**

EC50/24h >100 mg/l (daphnia magna)

**108-88-3 toluene**

NOEC/72h 10 mg/l (Skeletonema costatum)  
EC50/3h 134 mg/l (Chlorella vulgaris)

(Contd. on page 9)



Trade name: **Perfect Line Uni Thinner**

(Contd. of page 8)

- NOEC/7d 0.74 mg/l (Ceriodaphnia dubia)
- LOEC/7d 2.76 mg/l (Ceriodaphnia dubia)
- NOEC/40d 1.39 mg/l (Oncorhynchus kisutch)
- LOEC/40d 2.77 mg/l (Oncorhynchus kisutch)
- EC50/48h 3.78 mg/l (daphnia magna)
- EC50/7d 3.23 mg/l (Ceriodaphnia dubia)
- LC50/96h 5.5 mg/l (Oncorhynchus kisutch)
- 12.2 Persistence and degradability No further relevant information available.
- Degree of elimination:

**123-86-4 n-butyl acetate**

- OECD 301D 83 % (/) (28 d)
- 12.3 Bioaccumulative potential

**1330-20-7 xylene**

- BCF 25.9 (/)
- LogPow 3.15 (/)

**108-88-3 toluene**

- BCF 90 (/)
- LogPow 2.73 (/)
- 12.4 Mobility in soil No further relevant information available.
- Ecotoxicological effects:
- Remark: Harmful to fish
- Additional ecological information:
- General notes:
- Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Harmful to aquatic organisms
- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

**SECTION 13: Disposal considerations**

- 13.1 Waste treatment methods
- Recommendation  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- European waste catalogue  
07 01 04\* other organic solvents, washing liquids and mother liquors
- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

**SECTION 14: Transport information**

- 14.1 UN-Number
- ADR/ADN, IMDG, IATA UN1263
- 14.2 UN proper shipping name
- ADR/ADN 1263 PAINT RELATED MATERIAL
- IMDG, IATA PAINT RELATED MATERIAL

(Contd. on page 10)

Trade name: **Perfect Line Uni Thinner**

(Contd. of page 9)

- 14.3 Transport hazard class(es)
- ADR/ADN, IMDG, IATA



- Class 3 Flammable liquids.
- Label 3
- 14.4 Packing group
- ADR/ADN, IMDG, IATA III
- 14.5 Environmental hazards:
- Marine pollutant: No
- 14.6 Special precautions for user Warning: Flammable liquids.
- Danger code (Kemler): 30
- EMS Number: F-E,S-E
- Stowage Category A
- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.

- Transport/Additional information:

- ADR/ADN
- Limited quantities (LQ) 5L
- Excepted quantities (EQ) Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml
- Transport category 3
- Tunnel restriction code D/E

- IMDG
- Limited quantities (LQ) 5L
- Excepted quantities (EQ) Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml
- UN "Model Regulation": UN 1263 PAINT RELATED MATERIAL, 3, III

## SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
  - Directive 2012/18/EU
  - Named dangerous substances - ANNEX I None of the ingredients is listed.
  - Seveso category P5c FLAMMABLE LIQUIDS
  - Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t
  - Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t
  - REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- National regulations:
- Other regulations, limitations and prohibitive regulations  
The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 11)

Trade name: **Perfect Line Uni Thinner**

(Contd. of page 10)

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H361d Suspected of damaging the unborn child.
- H373 May cause damage to the central nervous system, the kidneys and the liver through prolonged or repeated exposure. Route of exposure: Inhalation.
- H412 Harmful to aquatic life with long lasting effects.

· Department issuing SDS: Product safety department.

· Contact: Ing. R. Derks

· Abbreviations and acronyms:

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- ICAO: International Civil Aviation Organisation
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- DNEL: Derived No-Effect Level (REACH)
- PNEC: Predicted No-Effect Concentration (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 3: Flammable liquids – Category 3
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- Repr. 2: Reproductive toxicity – Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
- Asp. Tox. 1: Aspiration hazard – Category 1
- Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3