



Printing date 18.12.2019 Revision: 18.12.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Perfect Line 1K Spotprimer White
- · Article number (product ID.): PL.SP.VS1
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Application of the substance / the mixture: painting
- · Uses advised against No further relevant information available.
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Perfect Line

P.O. Box 90117 T: +31 (0) 857441118 5000 LA Tilburg (NL) E: info@perfectline.nl

Further information obtainable from: Product safety department

- · 1.4 Emergency telephone number: Tel.:+49 6269 95 20
- · national:

National Poisons Information Service, Birmingham

Tel.: 844 892 0111

· K-Nr. 0001

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)



Printing date 18.12.2019 Revision: 18.12.2019

Trade name: Perfect Line 1K Spotprimer - White

(Contd. of page 1)

· Hazard pictograms







GHS02

GHS05

· Signal word Danger

Hazard-determining components of labelling:

butan-1-ol n-butyl acetate

Epoxy resin with an average molecular weight of 700≤1200

propan-1-ol

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation. H318 Causes serious eye damage.

H317 May cause an allergic skin reaction. H336 May cause drowsiness or dizziness.

· Precautionary statements

If medical advice is needed, have product container or label at hand. P101

P102 Keep out of reach of children. P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use. P261 Avoid breathing vapours/spray.

Use only outdoors or in a well-ventilated area. P271 IF ON SKIN: Wash with plenty of water. P302+P352 Immediately call a POISON CENTER/doctor. P310

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Additional information: Without adequate ventilation, explosive atmosphere/gas mix may be created.
- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 115-10-6	dimethyl ether	25-<50%
EINECS: 204-065-8	♠ Flam. Gas 1, H220; Press. Gas C, H280	
Reg.nr.: 01-2119472128-37-xxxx		
CAS: 123-86-4	n-butyl acetate	10-<25%
EINECS: 204-658-1	🅸 Flam. Liq. 3, H226; 🗘 STOT SE 3, H336	
Reg.nr.: 01-2119485493-29-xxxx	¥ , , , , , , , , , , , , , , , , , , ,	
	(Cor	ntd on nage



Printing date 18.12.2019 Revision: 18.12.2019

Trade name: Perfect Line 1K Spotprimer - White

	(Co	ntd. of page 2)
CAS: 67-64-1	acetone	10-<25%
EINECS: 200-662-2	♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319; STOT SE 3,	
Reg.nr.: 01-2119471330-49-xxxx	H336	
CAS: 71-36-3	butan-1-ol	5-<10%
EINECS: 200-751-6	🚸 Flam. Liq. 3, H226; 📀 Eye Dam. 1, H318; 🚺 Acute Tox.	
Reg.nr.: 01-2119484630-38-xxxx	4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	
CAS: 71-23-8	propan-1-ol	1-<2.5%
EINECS: 200-746-9	🍪 Flam. Liq. 2, H225; 📀 Eye Dam. 1, H318; 🕦 Acute Tox.	
Reg.nr.: 01-2119486761-29-xxxx	4, H302; STOT SE 3, H336	
CAS: 25068-38-6	Epoxy resin with an average molecular weight of 700≤1200	1-<2.5%
NLP: 500-033-5	🕠 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
· Additional information: For the	wording of the listed hazard phrases refer to section 16.	

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media -
- · Suitable extinguishing agents: Cool container whit water
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

GB



Printing date 18.12.2019 Revision: 18.12.2019

Trade name: Perfect Line 1K Spotprimer - White

(Contd. of page 3)

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: None.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

|--|

115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

71-36-3 butan-1-ol

WEL Short-term value: 154 mg/m³, 50 ppm

71-23-8 propan-1-ol

WEL Short-term value: 625 mg/m³, 250 ppm Long-term value: 500 mg/m³, 200 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

(Contd. on page 5)



Printing date 18.12.2019 Revision: 18.12.2019

Trade name: Perfect Line 1K Spotprimer - White

(Contd. of page 4)

· Respiratory protection:



When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply.

· Protection of hands:

Protective gloves



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material

Gloves must be changed after every contamination.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

butyl rubber, 0,7mm

Eye protection:

Safety glasses



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Aerosol

Colour: According to product specification

Odour: CharacteristicOdour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined. **Initial boiling point and boiling range:** -24.9 °C

· Flash point: <0 °C

Without propellant gas.

· Flammability (solid, gas): Not applicable.

· Ignition temperature: 235 °C

· Decomposition temperature: Not determined.

· Auto-ignition temperature: Product is not selfigniting.

(Contd. on page 6)



Printing date 18.12.2019 Revision: 18.12.2019

Trade name: Perfect Line 1K Spotprimer - White

	(Contd. of page
Explosive properties:	Product is not explosive. However, formation of explosive air vapour mixtures are possible. Not determined.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	18.6 Vol %
· Vapour pressure at 20 °C:	3,400 hPa
Density:	Not determined.
Relative density	Not determined.
· Vapour density	Not determined.
Evaporation rate	Not applicable.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	83.6 %
	With propellant gas. Content given by weight.
VOC (EU)	83.62 %
Solids content:	16.4 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Oral LD50 8,710 mg/kg (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye damage.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

(Contd. on page 7)



Printing date 18.12.2019 Revision: 18.12.2019

Trade name: Perfect Line 1K Spotprimer - White

(Contd. of page 6)

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Must not reach sewage water or drainage ditch undiluted or unneutralised.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Ikke relevant.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

15 01 10* packaging containing residues of or contaminated by hazardous substances

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION I	14: Transport	information

· 14.1 UN-Number · ADR, IMDG, IATA	UN1950
· 14.2 UN proper shipping name	
$\cdot ADR$	1950 AEROSOLS
· IMDG	AEROSOLS

· IATA AEROSOLS, flammable

(Contd. on page 8)



Printing date 18.12.2019 Revision: 18.12.2019

 ${\it Trade name: Perfect Line 1K Spotprimer - White}$

	(Contd. of page
· 14.3 Transport hazard class(es)	
· ADR	
2	
·Class	2 5F Gases.
· Label	2.1
· IMDG, IATA	
2	
· Class	2.1
· Label	2.1
· 14.4 Packing group	
· ADR, IMDG, IATA	Void
	not classified
· 14.5 Environmental hazards:	M_{\circ}
Marine pollutant:	No
· 14.6 Special precautions for user · Danger code (Kemler):	Warning: Gases.
Dunger coue (Kemier).	not classified
· EMS Number:	F- D , S - U
· Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of 1 lite Category A. For AEROSOLS with a capacity above 1 lite
	Category B. For WASTE AEROSOLS: Category C, Cle
	of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre
	Segregation as for class 9. Stow "separated from" class except for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class 2.
	For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
1477	
· 14.7 Transport in bulk according to Anne Marpol and the IBC Code	ex II of Not applicable.
· Transport/Additional information:	11
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0
Tuguan out a stanown	Not permitted as Excepted Quantity
Transport category Tunnel restriction code	2 D
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity



Printing date 18.12.2019 Revision: 18.12.2019

Trade name: Perfect Line 1K Spotprimer - White

(Contd. of page 8)

· UN "Model Regulation":

UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture VOC: <840g/l
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:
- · Technical instructions (air):

Class	Share in %
NK	50-100

- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

· Department issuing SDS: Product safety department

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases – Category 1

Aerosol 1: Aerosols – Category 1

Press. Gas C: Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

(Contd. on page 10)





Printing date 18.12.2019 Revision: 18.12.2019

Trade name: Perfect Line 1K Spotprimer - White

(Contd. of page 9)

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - oral – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

* Data compared to the previous version altered.